

LED liniar lamp, clear RL-RAL2 35 DIM 6W/230/827/C/S14S


Logistic Data

Article No.	42514766
Code	RL-RAL2 35 DIM 6W/230/827/C/S14S
Product EAN	4008597147661
Customs tariff no.	85437090
Box quantity (pcs.)	5
EAN Box	4008597447662
Gross weight of box in kg	0.727
Length of box in m	0.35
Width of box in m	0.26
Height of box in m	0.08
Pieces per palette	1100
ETIM class	EC001959
ETIM class name	LED lamp / Multi-LED




Electric Parameters

Lamp nominal wattage	6 W
Rated wattage	6.0 W
Comparable Wattage incandescent lamp	35 W
Mains voltage	230 V
Nominal current	26 mA
Power factor	0,62
Energy Consumption kWh/1000h	6
Nominal voltage from/ to	230 V



Light Application Parameters

Luminous flux	300 lm
Rated lamp luminous flux	300 lm
Luminous efficiency	50 lm/W
Radium light colour	warmwhite
Colour temperature	2700 K
Colour rendering index Ra	> 80
Colour rendering group	80-89 (Klasse 1B)
Luminous flux in 90°-sector	250 lm



Service Life

Mean service life	20000 h
Info about service life	L70B50
No. switching cycles	50000

Specification

Diameter max.	29 mm
Length max.	300 mm
Length	300 mm
Dimmable	true
Energylabel from 2013	A
Ignition time	0.0 s
Run up time = min. 60% luminous flux	0 s
Mercury content	0.0 mg
Base	other
Lamp shape	Tube
Colour	white

Miscellaneous

Product brochure	LED Programme
------------------	---------------

Notes:

RaLEDina linear lamp with LED inside, dimmable, for 1:1 replacement of Ralina/ Kristallina® (incandescent). LED light does not contain UV or IR radiation.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage. The field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Notes

Base



S14s
IEC/EN 60061-1
sheet 7004-112-1


Spectrum

As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.


The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.

White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin.

Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.



RaLEDina: LED retrofit for Linear incandescent lamp 2700K



daylight(D 65)

Special features



Please, dump as special waste, **no ordinary household waste!**

General notes

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.



LumiAx Lichttechnik | Groothandel | Import | Projectadviesbureau in Verlichting
Correspondentie- en Afleveradres: Kromme Kolk 7 | 9354 TJ Zevenhuizen
Magazijn: Exportweg 6-10 | 9301 ZV Roden

info@lumiAx.nl | www.lumiAx.nl |

ENGINEERS IN LIGHTING